



**SPECIFICATION:**

TRASHSCREEN (TM) SHALL BE AS MANUFACTURED BY:  
 BEST MANAGEMENT PRODUCTS, INC.  
 53 MT. ARCHER RD.  
 LYME CT, 06371  
 800-504-8008  
 WWW.BMPINC.COM

**MATERIAL SHALL BE:**

304 NON-MAGNETIC STAINLESS STEEL MIN STD.

STANDARD PERFORATIONS SHALL BE .25" DIAM  
 (10MM, 5MM, AND OTHER OPTIONS AVAILABLE)

INLET AREA SHALL EXCEED INLET AREA FOR SNOOT

TRASHSCREEN SHALL BE SIZED SPECIFICALLY  
 FOR EACH SNOOT SIZE AS PER DIMESIONS LISTED

TOP OF SCREEN SHALL BE SE AT OUTLET PIPE  
 CENTER LINE WITH TOP OPEN FOR OVERFLOW OR  
 BYPASS CAPACITY

U.S. AND FOREIGN PATENTS PENDING

**TRASHSCREEN DIMENSIONS**

SNOUT SIZE	H	W	D	C
18F OR R*	21"	28"	14"	5"
24F OR R*	27"	36"	18"	7"
30FOR R*	32"	46"	23"	8"
36F	45"	50"	25"	9"
48F	47"	68"	34"	11"
52R/72	80"	68"	50"	14"

H= HEIGHT

W= WIDTH

D= DEPTH

C= CLEARANCE FROM BOTTOM OF SCREEN

\*R SERIES SNOOTS REQUIRE ADAPTER AT  
 EXTRA COST

**BMP, INC.**

53 MT. ARCHER ROAD, LYME, CT. 06371  
 (800) 504-8008 FAX: (860)434-3195

DESCRIPTION TRASHSCREEN DIMENSIONS & SPECIFICATION	DATE 6-30-08	SCALE NONE
	DRAWING NUMBER <b>STSDIMSPEC</b>	