



SPECIFICATION:
 TRASHSCREEN (TM) SHALL BE AS MANUFACTURED BY:
 BEST MANAGEMENT PRODUCTS, INC.
 53 MT. ARCHER RD.
 LYME CT, 06371
 800-504-8008
 WWW.BMPINC.COM

MATERIAL SHALL BE:
 304 NON-MAGNETIC STAINLESS STEEL MIN STD.

STANDARD PERFORATIONS SHALL BE .25" DIAM
 (10MM, 5MM, AND OTHER OPTIONS AVAILABLE)

INLET AREA SHALL EXCEED INLET AREA FOR SNOOT

TRASHSCREEN SHALL BE SIZED SPECIFICALLY
 FOR EACH SNOOT SIZE AS PER DIMENSIONS LISTED

TOP OF SCREEN SHALL BE SET AT OUTLET PIPE
 CENTER LINE WITH TOP OPEN FOR OVERFLOW OR
 BYPASS CAPACITY

U.S. AND FOREIGN PATENTS PENDING

TRASHSCREEN DIMENSIONS

SNOUT SIZE	H	W	D	C
12F or R*	15"	22"	11"	2.5"
18F OR R*	21"	28"	14"	5"
24F OR R*	27"	36"	18"	7"
30FOR R*	32"	46"	23"	8"
36F	45"	50"	25"	9"
48F	47"	68"	34"	11"
52R/72	80"	68"	50"	14"

H= HEIGHT W= WIDTH D= DEPTH
 C= CLEARANCE FROM BOTTOM OF SCREEN
 *R SERIES SNOOTS REQUIRE ADAPTER AT
 EXTRA COST

BMP, INC.

53 MT. ARCHER ROAD, LYME, CT. 06371
 (800) 504-8008 FAX: (860)434-3195

DESCRIPTION TRASHSCREEN DIMENSIONS & SPECIFICATION	DATE 6-30-08	SCALE NONE
	DRAWING NUMBER STSDIMSPEC	