



SPECIFICATION:
 TRASHSCREEN (TM) SHALL BE AS MANUFACTURED BY:
 BEST MANAGEMENT PRODUCTS, INC.
 9 MATTHEWS DRIVE, UNIT A1-A2
 EAST HADDAM, CT 06423
 800-504-8008
 WWW.BMPINC.COM

MATERIAL SHALL BE:
 304 NON-MAGNETIC STAINLESS STEEL MIN STD.

STANDARD PERFORATIONS SHALL BE .25" DIAM**

**CUSTOM PERFORATIONS MAY BE AVAILABLE.
 SMALLER PERFORATIONS WILL RESULT IN
 GREATER HEIGHT SCREENS (H)

INLET AREA SHALL EXCEED INLET AREA FOR SNOUT

TRASHSCREEN SHALL BE SIZED SPECIFICALLY
 FOR EACH SNOUT SIZE AS PER DIMENSIONS LISTED

TOP OF SCREEN SHALL BE SET AT OUTLET PIPE
 CENTER LINE OR HIGHER

U.S. AND FOREIGN PATENTS PENDING

TRASHSCREEN DIMENSIONS				
SNOUT SIZE	H	W	D	C
18F OR R*	21"	28"	14"	5"
24F OR R*	27"	36"	18"	7"
30FOR R*	32"	46"	23"	8"
36F	45"	50"	25"	9"
48F	47"	68"	34"	11"
52R/72	80"	68"	50"	14"

H= HEIGHT
 W= WIDTH
 D= DEPTH
 C= CLEARANCE FROM BOTTOM OF SCREEN
 *R SERIES SNOUTS REQUIRE ADAPTER AT
 EXTRA COST

BMP, INC.

9 MATTHEWS DR. UNIT A1-A2
 E. HADDAM, CT. 06371
 (800) 504-8008 FAX: (860)434-3195

DESCRIPTION TRASHSCREEN DIMENSIONS & SPECIFICATION	DATE 6-30-18	SCALE NONE
	DRAWING NUMBER STSDIMSPEC	